

MATERIAL SAFETY DATA SHEET

B50WW7
04 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

B50WW7

HMIS CODES

| | |
|--------------|----|
| Health | 2* |
| Flammability | 3 |
| Reactivity | 0 |

PRODUCT NAME

STEEL SPEC* Structural Steel Primer, Off White

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY
101 Prospect Avenue N.W.
Cleveland, OH 44115

EMERGENCY TELEPHONE NO.
(216) 566-2917

DATE OF PREPARATION
25-MAY-04

INFORMATION TELEPHONE NO.
(216) 566-2902

| Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS | | | | | | | |
|---|------------|------------------------|-----------------------------|----------------|--|--|---------|
| % by WT | CAS No. | INGREDIENT | UNITS | VAPOR PRESSURE | | | |
| 2 | 100-41-4 | Ethylbenzene | | | | | |
| | | ACGIH TLV | 100 ppm | | | | 7.1 mm |
| | | ACGIH TLV | 125 ppm STEL | | | | |
| | | OSHA PEL | 100 ppm | | | | |
| | | OSHA PEL | 125 ppm STEL | | | | |
| 14 | 1330-20-7 | Xylene | | | | | |
| | | ACGIH TLV | 100 ppm | | | | 5.9 mm |
| | | ACGIH TLV | 150 ppm STEL | | | | |
| | | OSHA PEL | 100 ppm | | | | |
| | | OSHA PEL | 150 ppm STEL | | | | |
| 2 | 107-87-9 | Methyl n-Propyl Ketone | | | | | |
| | | ACGIH TLV | 200 ppm | | | | 27.8 mm |
| | | ACGIH TLV | 250 ppm STEL | | | | |
| | | OSHA PEL | 200 ppm | | | | |
| | | OSHA PEL | 250 ppm STEL | | | | |
| 0.2 | 14808-60-7 | Quartz | | | | | |
| | | ACGIH TLV | 0.05 mg/m3 as Resp. Dust | | | | |
| | | OSHA PEL | 0.1 mg/m3 as Resp. Dust | | | | |
| 5 | 14807-96-6 | Talc | | | | | |
| | | ACGIH TLV | 2 mg/m3 as Resp. Dust | | | | |
| | | OSHA PEL | 2 mg/m3 as Resp. Dust | | | | |
| 39 | 471-34-1 | Calcium Carbonate | | | | | |
| | | ACGIH TLV | 10 mg/m3 as Dust | | | | |
| | | OSHA PEL | 15 mg/m3 Total Dust | | | | |
| | | OSHA PEL | 5 mg/m3 Respirable Fraction | | | | |
| 11 | 13463-67-7 | Titanium Dioxide | | | | | |
| | | ACGIH TLV | 10 mg/m3 as Dust | | | | |
| | | OSHA PEL | 10 mg/m3 Total Dust | | | | |
| | | OSHA PEL | 5 mg/m3 Respirable Fraction | | | | |

Continued on page 2

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

Section 4 -- FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes.
Get medical attention.SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.INHALATION: If affected, remove from exposure. Restore breathing.
Keep warm and quiet.INGESTION: Do not induce vomiting.
Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT

90 F PMCC

LEL

1.0

UEL

8.7

FLAMMABILITY CLASSIFICATION

RED LABEL -- Flammable, Flash below 100 F

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Continued on page 3

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove all sources of ignition. Ventilate the area.
Remove with inert absorbent.

Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY

DOL Storage Class IC,

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Contents are FLAMMABLE. Keep away from heat, sparks, and open flame.
During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.
Consult NFPA Code. Use approved Bonding and Grounding procedures.
Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.
Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.
Wash hands after using.
This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|----------------------------|-------------------|--|
| PRODUCT WEIGHT | 13.84 lb/gal | 1658 g/l |
| SPECIFIC GRAVITY | 1.67 | |
| BOILING POINT | 217 - 292 F | 102 - 144 C |
| MELTING POINT | Not Available | |
| VOLATILE VOLUME | 36 % | |
| EVAPORATION RATE | Slower than ether | |
| VAPOR DENSITY | Heavier than air | |
| SOLUBILITY IN WATER | N.A. | |
| VOLATILE ORGANIC COMPOUNDS | (VOC Theoretical) | |
| 2.61 lb/gal | 313 g/l | Less Water and Federally Exempt Solvents |
| 2.61 lb/gal | 313 g/l | Emitted VOC |

Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable
CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

Ethylbenzene is classified by IARC as possibly carcinogenic to humans (2B) based on inadequate evidence in humans and sufficient evidence in laboratory animals. Lifetime inhalation exposure of rats and mice to high ethylbenzene concentrations resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. These effects were not observed in animals exposed to lower concentrations. There is no evidence that ethylbenzene causes cancer in humans.

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary and reproductive systems.

Rats exposed to titanium dioxide dust at 250 mg./m³ developed lung cancer, however, such exposure levels are not attainable in the workplace.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

TOXICOLOGY DATA

Continued on page 5

| CAS No. | Ingredient Name | | | | |
|------------|------------------------|--------------|------------|-----|--------------------------------|
| 100-41-4 | Ethylbenzene | LC50 LD50 | RAT RAT | 4HR | Not Available 3500 mg/kg |
| 1330-20-7 | Xylene | LC50 LD50 | RAT RAT | 4HR | 5000 ppm 4300 mg/kg |
| 107-87-9 | Methyl n-Propyl Ketone | LC50 LD50 | RAT RAT | 4HR | Not Available 1600 mg/kg |
| 14808-60-7 | Quartz | LC50 LD50 | RAT RAT | 4HR | Not Available Not Available |
| 14807-96-6 | Talc | LC50 LD50 | RAT RAT | 4HR | Not Available Not Available |
| 471-34-1 | Calcium Carbonate | LC50 LD50 | RAT RAT | 4HR | Not Available Not Available |
| 13463-67-7 | Titanium Dioxide | LC50 LD50 | RAT RAT | 4HR | Not Available Not Available |

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Section 14 -- TRANSPORT INFORMATION

No data available.

Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

| CAS No. | CHEMICAL/COMPOUND | % by WT | % Element |
|-----------|-------------------|---------|-----------|
| 100-41-4 | Ethylbenzene | 2 | |
| 1330-20-7 | Xylene | 14 | |

Continued on page 6

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.