

**SCS 1200 Construction Clear
Silicone sealant (adhesive)****1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Manufactured By: Momentive performance material
260 Hudson River Rd
Waterford NY 12188

Revised: 04/05/2011
Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Sealant
Formula: MixtureSilicone sealant

HMIS

Flammability: 1 Reactivity: 0 Health: 2

NFPA

Flammability: 1 Reactivity: 0 Health: 2

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

WARNING! Irritating to eyes, respiratory system and skin. May be harmful if swallowed. Adverse liver and reproductive effects reported in animals.

Form: Paste

Color: Colorless

Odor: Acetic acid.

POTENTIAL HEALTH EFFECTS**INGESTION**

May be harmful if swallowed.

SKIN

May cause mild skin irritation.

INHALATION

None known.

EYES

May cause eye irritation.

MEDICAL CONDITIONS AGGRAVATED

None known.

SUBCHRONIC (TARGET ORGAN)

Liver injury.; Reproductive hazard.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or

**SCS 1200 Construction Clear
Silicone sealant (adhesive)**

suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Dermal; Eye

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<u>A. HAZARDOUS</u>		
Methyltriacetoxysilane	4253-34-3	1 - 5 %
Octamethylcyclotetrasiloxane	556-67-2	1 - 5 %
<u>B. NON-HAZARDOUS</u>		
Dimethylpolysiloxane	70131-67-8	60 - 100 %
Siloxanes & Silicones, Dimethylpolymers w/Methylsilsesquioxanes	68554-67-6	5 - 10 %
Treated Filler	68611-44-9	10 - 30 %

4. FIRST AID MEASURES**INGESTION**

DO NOT induce vomiting. Get medical attention immediately.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

NOTE TO PHYSICIAN

None known.

**SCS 1200 Construction Clear
Silicone sealant (adhesive)****5. FIRE-FIGHTING MEASURES**

FLASH POINT: > 93.3 °C; 200 °F
METHOD: Estimated
IGNITION TEMPERATURE: Not applicable
FLAMMABLE LIMITS IN AIR - LOWER (%): Not applicable
FLAMMABLE LIMITS IN AIR - UPPER (%): Not applicable

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES**ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. HANDLING AND STORAGE**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Avoid contact with eyes, skin, and clothing. Wash hands before eating, drinking, or smoking. Use only in well-ventilated areas. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the finger and hands. Residual sealant may remain on fingers for several days and transfer to lenses, resulting in eye irritation.

Store away from heat, sources of ignition, and incompatibles. Keep out of reach of children. Keep container closed.

STORAGE

Keep container tightly closed in a cool, well-ventilated place.

**SCS 1200 Construction Clear
Silicone sealant (adhesive)****8. EXPOSURE CONTROLS/PERSONAL PROTECTION****ENGINEERING CONTROLS**

Eye wash facilities and emergency shower must be available when handling this product.; Showers;
Exhaust ventilation

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Butyl rubber gloves are recommended.

EYE AND FACE PROTECTION

Monogoggles; Face shield

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
-------------------------	----------------------	----------------------	---------------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	No data available.
VAPOR PRESSURE (20 C) (MM HG):	No data available.
VAPOR DENSITY (AIR=1):	Not applicable
FREEZING POINT:	No data available.
PHYSICAL STATE:	Paste
Odor:	Acetic acid.
Color:	Colorless
EVAPORATION RATE (BUTYL ACETATE=1):	< 1
SPECIFIC GRAVITY (WATER=1):	ca. 1.06
DENSITY:	ca. 1.06 g/cm3
ACID / ALKALINITY (MEQ/G):	Not applicable
pH:	Not applicable
SOLUBILITY IN WATER (20 C):	No data available.

**SCS 1200 Construction Clear
Silicone sealant (adhesive)**

SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT): Toluene

10. STABILITY AND REACTIVITY**STABILITY**

Stable

HAZARDOUS POLYMERIZATION

Hazardous polymerisation does not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide; Acetic acid.; Silicon dioxide.; Formaldehyde.; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION**ACUTE ORAL**

Remarks: No data available.

ACUTE DERMAL

Remarks: No data available.

ACUTE INHALATION

Remarks: No data available.

OTHER

Octamethylcyclotetrasiloxane

Ingestion: Rodents given large doses via oral gavage of octamethylcyclotetrasiloxane (1600 mg/kg day, 14 days) developed increased liver weights relative to unexposed control animals due to hepatocellular hyperplasia (increased number of liver cells which appear normal) as well as hypertrophy (increased cell size).

Inhalation: In inhalation studies, laboratory rodents exposed to octamethylcyclotetrasiloxane (300 ppm five days week, 90 days) developed increased liver weights in female animals relative to unexposed control animals. When the exposure was stopped, liverweights returned to normal. Microscopic examination of the liver cells did not show any evidence of pathology. Inhalation studies utilizing

**SCS 1200 Construction Clear
Silicone sealant (adhesive)**

laboratory rabbits and guinea pigs showed no effects on liver weights. Inhalation exposures typical of industrial usage (5-10 ppm) showed no toxic effects in rodents.

Range finding reproductive studies were conducted (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) with octamethylcyclotetrasiloxane (D4). Rats were exposed to 70 and 700 ppm. In the 700 ppm group, there was a statistically significant reduction in mean litter size and in implantation sites. No D4 related clinical signs were observed in the pups and no exposure related pathological findings were found.

Interim results from a two generation reproductive study in rats exposed to 500 and 700 ppm D4 (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) resulted in a statistically significant decrease in live mean litter size as well as extended periods of off-spring delivery (dystocia). These results were not observed at the 70 and 300 ppm dosing levels.

Preliminary results from an ongoing 24-month combined chronic/oncogenicity study in rats exposed to 10, 30, 150, or 700 ppm D4 showed test-article related effects in the kidney (male and female) and uterus of rats exposed for 12 to 24 months. These effects include increased kidney weight and severity of chronic nephropathy, increased uterine weight, increased incidence of endometrial cell hyperplasia, and an increased incidence of endometrial adenomas. All of these effects are limited to the 700 ppm exposure group.

These results have been shown to be rat-specific. Further studies are ongoing.

In developmental toxicity studies, rats and rabbits were exposed to octamethylcyclotetrasiloxane at concentrations up to 700 ppm and 500 ppm respectively. No teratogenic effects (birth defects) were observed in either study.

SENSITIZATION

No data available.

SKIN IRRITATION

No data available.

EYE IRRITATION

No data available.

MUTAGENICITY

No data available.

OTHER EFFECTS OF OVEREXPOSURE

This product contains methyl polysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive., Acetic acid released during curing., Contains octamethylcyclotetrasiloxane which may cause reproductive effects based on animal data.

**SCS 1200 Construction Clear
Silicone sealant (adhesive)****12. ECOLOGICAL INFORMATION****ECOTOXICITY**

Ecotoxicological data for this product is not available.

DISTRIBUTION

No data available.

CHEMICAL FATE

No data available.

13. DISPOSAL CONSIDERATIONS**DISPOSAL METHOD**

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION**Further Information:**

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION**Inventories**

Australia Inventory of Chemical Substances (AICS)	y (positive listing)	
EU list of existing chemical substances	y (positive listing)	
Japan Inventory of Existing & New Chemical Substances (ENCS)	y (positive listing)	
China Inventory of Existing Chemical Substances	y (positive listing)	
Korea Existing Chemicals Inventory (KECI)	y (positive listing)	
Canada DSL Inventory	y (positive listing)	
Canada NDSL Inventory	n (Negative listing)	
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (positive listing)	
TSCA list	y (positive listing)	On TSCA Inventory
For inventories that are marked as quantity restricted or special cases, please contact Momentive.		

**SCS 1200 Construction Clear
Silicone sealant (adhesive)**

US Regulatory Information**SARA (311,312) HAZARD CLASS**

Acute Health Hazard

SARA (313) CHEMICALS**CALIFORNIA PROPOSITION 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Canadian Regulatory Information**WHMIS HAZARD CLASS**

D2A - Very Toxic Material Causing Other Toxic Effects

D2B - Toxic Material Causing Other Toxic Effects

16. OTHER INFORMATION**OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

,C = ceiling limit NEGL = negligible
EST = estimated NF = none found
NA = not applicable UNKN = unknown
NE = none established REC = recommended
ND = none determined V = recommended by vendor
SKN = skin TS = trade secret
R = recommended MST = mist
NT = not tested STEL = short term exposure limit
ppm = parts per million ppb = parts per billion

By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).