

MATERIAL SAFETY DATA SHEET

No. J97-191, Rev. D

Dated 05/20/98

Section 1. COMPANY AND PRODUCT IDENTIFICATION

Manufacturer's Name : Ampco Metal
1745 South 38TH Street, P.O. Box 2004
Milwaukee, WI 53201

Telephone Number : (414) 645-3750 (USA), 7:30 AM - 5:00 PM
(Central or Central Daylight Time)

Material Name : Copper Base Alloy Castings, Rods, Bars,
Tubes, Shapes, Flat Products, Scrap Materials
and Safety Tools.

These materials are commonly referred to as High-Copper
Alloys, Aluminum Bronzes, Silicon Bronzes, Manganese
Bronzes and Copper-Nickel Alloys.

Section 2. Composition / Information On Components

Individual AMPCO Alloy compositions are shown on the Certification of Chemical and Mechanical Properties, when supplied, or may be found in AMPCO promotional literature such as bulletins: G-51, G-100, G-120, etc.

<u>Component</u>	<u>CAS No.</u>	<u>Percent</u>	<u>OSHA PEL</u> <u>8 - Hr TWA</u> <u>Milligrams Per Cubic Meter</u>	<u>ACGIH-TLV</u> <u>8-Hr TWA</u>
<u>Aluminum**</u>	<u>7429-90-5</u>	<u>0-20</u>		
Metal		Dust	15	10
		Fume	5	5

<u>Beryllium</u>	<u>7440-41-7</u>	<u>See Below</u>	<u>0.002</u>	<u>0.002</u>
			NOTE: beryllium is present only in some special tools.	
<u>Chromium*</u>	<u>7440-47-3</u>	<u>0-2</u>		
Metal			1	0.5
<u>Cobalt*</u>	<u>7440-48-4</u>	<u>0-3</u>		
Metal		Dust and Fume	0.05	0.05
<u>Copper*</u>	<u>7440-50-8</u>	<u>50-100</u>		
Metal		Dust	1	1
		Fume	0.1	0.2
<u>Iron</u>	<u>7439-89-6</u>	<u>0-6</u>		
Iron Oxide		Dust and Fume	10	5
<u>Lead*</u>	<u>7439-92-1</u>	<u>0-11</u>		
Metal		Inorganic Dust and Fume	0.05	0.15
<u>Manganese*</u>	<u>7439-96-5</u>	<u>0-14</u>		
Metal		Dust	5	5
		Fume	1	1
<u>Nickel*</u>	<u>7440-02-0</u>	<u>0-32</u>		
Metal and Insoluble Compounds			1	1
<u>Niobium</u>	<u>7440-03-1</u>	<u>0-3</u>		
Metal			None Established	
<u>Silicon</u>	<u>7440-21-3</u>	<u>0-4</u>		
		Dust	10	10
<u>Tin</u>	<u>7440-31-5</u>	<u>0-20</u>		
Oxide and inorganic compounds			2	2
<u>Zinc**</u>	<u>7440-66-6</u>	<u>0-42</u>		
Oxide		Dust	10	10
		Fume	5	5
<u>Zirconium</u>	<u>7440-67-7</u>	<u>0-0.5</u>		
Metal			5	5

Elements having a listed percentage greater than zero will be present in all alloy grades. Elements having percentages starting with zero may not be present in certain alloy grades.

* This constituent, a toxic chemical, makes this product subject to the reporting requirements of section 313 of title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. Quantity threshold for this chemical, below which reporting of releases is not required, is 25,000 pounds.

** This constituent is reportable only if in the form of dust or fume.

Note : Chromium , lead and nickel have been identified as potential human carcinogens.

Note : Zinc, Manganese, Tin, Lead, Silicon, Cobalt, Chromium, and Beryllium may be present in excess of 1%.

Section 3. HAZARDOUS IDENTIFICATION

Emergency Overview

There are no chemical hazards from those alloy grades in the solid form.

Potential Health Effects

Machining, grinding, flame-cutting or welding of these alloy products will put contaminants, primarily copper, in the air. Aluminum, cobalt, manganese, nickel or zinc may be present if part of the specific alloy grade. If copper dust and fumes are adequately controlled, the other named metals and any unnamed metals which may be present in the alloy will not represent a hazard.

Beryllium and its compounds are considered to be human and experimental carcinogens, tumorigens, and neoplastigens. Beryllium compounds can enter the body through inhalation of dust and fumes, and may act locally on the skin. Even alloys of low beryllium content have been shown to be dangerous.

Copper fumes and dust irritate the nose and throat. If too much fume is inhaled, it will cause a sweet or metallic taste in the mouth. High concentrations of the fumes can cause metal fume fever, which resembles the flu. Inhaling excessive amounts of

J79-191D

copper dust and fume over a long period of time can cause anemia. The dust may also cause skin and eye irritation after short exposure.

Some forms of nickel have been found to cause cancer in animals. One form, nickel subsulfide, which was present in an old smelting process no longer used, was the apparent cause of lung and nasal cancer in humans. Since then, studies have shown that the potential for ordinary forms of nickel and its oxides to cause cancer in humans is very weak, if it exist at all.

Long, continued exposure to manganese dust or fume causes a number of symptoms which can get quite serious. On the other hand, manganese is an essential trace element for human metabolism and an average daily intake of 2 to 5 mg, mostly in food, is necessary for health. This intake is about 20% to 50% of the intake resulting from the PEL and TLV of 1 mg/cu.m air.

Excessive manganese effects the central nervous system, with the following symptoms in order of increasing exposure: apathy, loss of appetite, uncontrolled laughter, insomnia followed by sleepiness, headache, leg cramps, speech disturbances, mask-like facial appearance, clumsy movement, difficult walking, frequent falling, tremors, salivating, sweating, mental detachment.

High production machining, grinding and welding operations, etc. frequently require local exhaust ventilation. If ventilation is not adequate, wear a NIOSH approved dust and fume respirator.

Grinding on castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing free silica, which can cause silicosis. IARC has listed crystalline silica as Class 2A, probably can cause lung cancer.

CARCINOGEN CLASSIFICATION

<u>Ingredient</u>	<u>OSHA NTP</u>		<u>IARC</u>	<u>TARGET ORGAN</u>
Beryllium	N	Y	2B	Lung
Chromium	N	Y	3	Lung
Hexavalent Cr	N	Y	1	Lung
Lead	N	N	2B	Lung, Stomach
Nickel	N	Y	1	Lung, Stomach

N = Not listed as a Human Carcinogen

Y = Listed as a Human Carcinogen

Code for IARC evidence of human carcinogenicity : 1 = Positive;
2A = Probable; 2B = Possible; 3 = Not Classified; 4 = Probably Negative.

Section 4. FIRST AID MEASURES

- Eye Contact : Flush well with running water to remove particulate. Get medical attention.
- Skin Contact : Vacuum off excess dust. Wash well with soap and water. Avoid blowing particulate into the atmosphere. Contact with these alloy grades in the molten condition will cause severe burns. Get medical attention.
- Inhalation : Remove to fresh air. Get medical attention.
- Ingestion : Seek medical attention if large quantities of material have been ingested. (Unlikely in the state as sold, tools.)

J79-191D

Section 5.

FIRE FIGHTING MEASURES

Flash Point : Not Applicable **Methods Used :** Not Applicable

Flammable Limits : LFL : Not Applicable
UFL : Not Applicable

Extinguishing Media : See Below

Special Fire Fighting Procedures : Solid, massive form is not combustible under normal conditions. Use fire fighting methods that are appropriate for surrounding fire.

Small chips, fine turnings and dust may ignite readily. Use coarse water spray on chips, turnings, etc. Use Class D extinguishing agents or dry sand on fines. **DO NOT** use halogenated agents on small chips or fines. Dust clouds may be explosive. **PREVENT FORMATION OF A DUST CLOUD.**

Molten metal alloys may explode on contact with water. They may also react violently with water, rust and certain other metal oxides (e.g. oxides of copper, iron and lead).

Firefighters should wear self contained breathing apparatus and protective clothing.

Section 6. ACCIDENTAL RELEASE MEASURES

There are no hazards from these alloy grades in solid form.

Vacuum or sweep material and place in a disposal container. Wear protective gloves to avoid cuts from burrs or sharp edges when handling larger pieces for disposal.

J79-191D

Section 7. HANDLING AND STORAGE

No special precautions are necessary for bulk materials. Store material away from incompatible materials and keep dust of fines away from source of ignition.

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection : If the exposure above the PEL or TLV, NIOSH approved respirator for fume or dust, dependent upon the source of airborne contaminant.

Ventilation : Required if dust or fume created in handling or working on this material.

Local Exhaust : Required if dust or fume created in handling or working on this material.

Mechanical (General) : As above to reduce airborne dust or fume.

Protective Gloves : Required for melting, grinding, cutting or welding operations. Select glove approved for the specific operation.

Eye Protection : Required for melting, grinding, cutting or welding operations. Minimum requirement of safety glasses with side shields for these operations. Melting and welding may require special eye protection including face shields and specially tinted glass and/or welder's helmet. Grinding operations may require face shields.

Other Protective Clothing or Equipment : Use leather or equal protective gloves and body clothing while welding. As required for all other operations performed in the product.

Work / Hygiene Practices : Use ear muffs or plugs if the noise level is above 90 dBA when performing operations on the product. Always evaluate the operations done on this product in accordance with OSHA or relevant state, federal or local standards.

J79-191D

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and odor :	Silver / grey, yellow or reddish color with no odor.
Melting Point (F) :	Approximately 1600-2100 depending on specific alloy grade. Alloys have a range of temperature over which melting occurs.
Specific Gravity :	Approximately 8.1-8.9 depending on specific alloy grade.
Vapor Pressure :	Not Applicable.
Vapor Density :	Not Applicable.
% Volatile By Volume :	Not Applicable.
Evaporation Rate :	Not Applicable.
Solubility in Water :	Insoluble.

Section 10. STABILITY AND REACTIVITY

<u>Chemical Stability :</u>	Stable under normal conditions of use, storage and transportation.
<u>Conditions to Avoid :</u>	Molten metal may react violently with water. Avoid contact of finely divided material with heat, oxidizers, acids, alkalis, molten lithium and halogenated compounds. Contact of dust or fumes with these substances may form explosive hydrogen gas.
<u>Incompatibility with Other Materials :</u>	Avoid acids, bases and oxidizers.
<u>Hazardous Decomposition products :</u>	Metal fume.
	J79-191D
<u>Hazardous Polymerization :</u>	Will not occur.

Section 11. TOXICOLOGY INFORMATION

Permissible Exposure Limits and Threshold Limit Values : See Section 2.

Route(s) of entry: Inhalation : Yes
 Skin : Yes
 Ingestion : Yes

Effects of Overexposure :

Aluminum

Aluminum dust / fines and fumes are a low health risk by inhalation and are normally treated as a nuisance dust in normal operations (e.g. milling, cutting and grinding) . The AIHA Hygiene Guide lists toxicity by ingestion by "none expected." Chronic exposure may cause pulmonary fibrosis characterized by breathing difficulty, coughing, shortness of breath, wheezing and other respiratory difficulties. Aluminum has been implicated in Alzheimer's disease.

Beryllium

Inhalation of Beryllium dust or fume may result in the production of an acute or chronic systematic disease depending upon the level of exposure and the beryllium compound involved. Granulomatous lesions of the skin, liver, kidneys, spleen and lymph nodes have been reported. Damage to the lungs may be in both the acute and chronic forms, both of which have similar signs and symptoms. These include a relatively non-productive cough, progressive difficulty in breathing, loss of appetite, and loss of weight. The major difference between the two is the suddenness of onset and the rate of progression. In the acute form, the symptoms appear in several hours to several weeks after exposure and there is usually rapid progression of signs including dyspnea, anorexia, an extreme weight loss. Complete recovery is possible and fatal cases usually result from acute heart disease.

In chronic beryllium disease, the symptoms or signs are generally delayed in their onset and are persistent in nature. They may be triggered or aggravated by stresses such as pregnancy, respiratory infection, and thyrotoxicosis. In the progression of the disease, symptoms of heart disease may occur. Beryllium is also a suspected human carcinogen and has caused cancer in laboratory animals.

J79-191D

Chromium

In some workers, chromium compounds act as allergens, may cause dermatitis and may also produce pulmonary sensitization. Chromic acid and chromates have a direct corrosive effect on the skin and the mucous membranes of the upper respiratory tract. Although rare, there may be the possibility of skin and pulmonary sensitization. IARC has determined that there is sufficient evidence of

increased lung cancer among workers in the chromate-producing industry and possible among chromium alloy workers. This determination is supported by sufficient evidence for carcinogenicity to animals and possible mutagenicity testing of Cr VI compounds.

Cobalt :

Cobalt has been reported as causing hypersensitization type dermatitis in individuals who are susceptible. Animal studies have shown that particulate cobalt is an acutely irritating substance and industrial exposures, possibly combined with small amounts of silica, are reported capable of producing serious pneumoconiosis which is initially of an insidious nature.

Copper

Melting, grinding and cutting of copper may produce fumes or dust exposure and breathing these fumes or dust may create potentially significant health hazards. Fumes from copper may cause metal fume fever with flu-like symptoms and skin and hair discoloration. While industrial dermatitis has not been reported, keratinization of the hands and the soles of the feet has been reported. Systemically as well, copper dust and fume cause irritation of the upper respiratory tract, metallic taste in the mouth and nausea. Chronic poisoning may result in Wilson's disease, characterized by damage to the blood cells, brain, kidneys, liver and pancreas. Symptoms include weakness, anemia, abdominal pain and yellowing of the skin.

Iron

The inhalation of iron oxide fumes may cause benign pneumoconiosis which is called siderosis. This disease is reported not to be disabling, but make X-ray determination of other lung conditions difficult or impossible.

Lead

Short Term Exposure: Lead is an accumulative poison. Inhalation effects of exposure to fumes or dust of inorganic lead may develop quickly. Symptoms include decreased physical fitness, fatigue, sleep disturbance, headache, aching bones and muscles, constipation, abdominal pains and decreasing appetite. The effects are reversible and complete recovery is possible. Inhalation of large amounts of lead may lead to seizures, comma and death.

J79-191D

Long Term Exposure: Long term exposure can result in a build up of lead in the body and more severe symptoms. These may include anemia, pale skin, a blue line at the gum margin, decreased hand grip strength, abdominal pain, severe constipation, nausea, vomiting and paralysis of the wrist joint. Prolonged exposure may also result in kidney damage. If the nervous system is affected usually due to very high exposures, the resulting effects include severe headache, convulsions,

delirium and death. Ingesting alcohol and physical exertion may bring on symptoms. Continued exposure can result in decreased fertility and/or increased chances of miscarriage or birth defects.

Manganese

Chronic manganese poisoning may result from inhalation of dust or fume. The central nervous system is the chief site of the injury. Chronic manganese poisoning is not a fatal disease although it is extremely disabling. Some individuals may be hypersusceptible to manganese. Freshly formed manganese fume has caused fever and chill similar to metal fume fever.

Nickel

The most common ailment arising from contact with nickel or its compounds is an allergic dermatitis known as "nickel itch" which usually occurs when the skin is moist. Generally nickel and most salts of nickel do not cause systematic poisoning. IARC has determined that there is at least limited evidence that nickel and certain nickel compounds may be human carcinogens. Several nickel compounds are carcinogenic to laboratory animals by various routes of entry.

Silicon

Silicon exposure poses little health risk with only minimal effects on the lungs. Silicon dioxide, silica, formed when silicon is heated in air may cause pulmonary fibroses and silicosis on chronic exposure. This is a form of pneumoconiosis which is characterized by the formation of the nodules of scar tissue (fibrosis) throughout the lungs. Silicosis can cause difficult or labored breathing especially on exertion, decreased physical work capacity and sometimes an enlarged chest.

Tin

The inhalation of inorganic tin fumes or dust may cause an apparent benign pneumoconiosis called stannosis which is reported not to be disabling.

J79-191D

Zinc

Zinc is relatively low in toxicity but inhalation of fumes may cause "metal fume fever." Onset of symptoms may be delayed four to twelve hours and include irritation of the nose, mouth and throat, cough, stomach pain, headache, nausea, vomiting, metallic taste, chills, fever, pains in the muscles and joints, thirst,

bronchitis or pneumonia and a bluish tint to the skin. These symptoms go away in twenty-four to forty-eight hours and leave no effect.

Zirconium

A study of twenty-two workers exposed to fumes from a zirconium reduction process for one to five years revealed no abnormalities referable to the exposure. There are no well-documented cases of toxic effects from industrial exposure. Granulomatous of the human axillary skin have occurred from the use of deodorants containing zirconium, although the metal is not regarded as a skin sensitizer in other types of exposure.

Section 12. ECOLOGICAL INFORMATION

No information is available.

Section 13. DISPOSAL CONSIDERATIONS

The alloy grades covered by this Material Safety Data Sheet are recyclable. The value of solids, turning, etc. will be increased when segregated by alloy grade. Recycling is recommended. Any disposal practice must be in compliance with local, state and federal laws and regulations (contact local or state environmental agency for specific rules).

Section 14. TRANSPORTATION INFORMATION

Not a Hazardous Material for DOT shipping.

J79-191D

Section 15. REGULATORY INFORMATION

See Section 2 for identification of alloy components which may be subject to SARA 313 regulation.

Section 16. OTHER INFORMATION

Revised to format of ANSI Standards Z400.1-1993.

The following hazard ratings are recommended for the alloy grade covered by this Material Safety Data Sheet :

<u>NFPA</u>		
Fires	-	0
Health	-	0
Reactivity	-	0
Specific Hazard	-	none

To the best of our knowledge, the information contained in this Material Safety Data Sheet is accurate. However, neither AMPCO METAL nor any of its representatives assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein we cannot guarantee that these are the only hazards which exists.

The tools sold by AMPCO Metals are articles as defined by the federal OSHA standards under 1910.1200. As such, in their use as tools in the workplace they should not generate dust or fumes. However, if any operations or work is done on the tool which might generate these dusts or fumes, please refer to the information on the characteristics of the metals used in the production of the tools as described in this Material Safety Data Sheet.

Please note, some tools contain small percentages of BERYLLIUM, a highly toxic metal which in the form sold as a tool should not present any hazards. However, if any work is done on the tools which would generate dust or fumes, refer to Control Measures section of this data sheet and TAKE ALL NECESSARY PRECAUTIONS in accordance with the information contained herein and all federal, state, and local regulations.