

TESCH CHEMICAL COMPANY

P.O. BOX 631
APPLETON, WI 54912

PAGE 1 OF 2

MATERIAL SAFETY DATA SHEET

DATE: 4/30/08

PRODUCT NO. : TC320

PHONE NO. : 414-739-7331

SECTION 1 - PRODUCT IDENTIFICATION

PRODUCT NO. : TC320

PRODUCT NAME : SPEEDEE SPARKLE

ATTN: PLANT MGR / SAFETY DIR.

PRODUCT CLASS : SPRAY ON WIPE OFF
GLASS CLEANER

SECTION 2 - HAZARDOUS INGREDIENTS

INGREDIENT:	PERCENT	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE
		TLV	PEL	
*CAS. NO.				
ISOPROPYL ALCOHOL *67-63-0	8.2%	400 PPM (SKIN)		33MM.HG

HAZARD RATING: HEALTH = 1 FLAMMABILITY = 3 REACTIVITY = 0

SECTION 3 - PHYSICAL DATA

BOILING RANGE: 180.1 DEG.F VAPOR DENSITY: HEAVIER LIGHTER THAN AIR
EVAPORATION RATE: FASTER SLOWER THAN ETHER 8% VOLATILE
WEIGHT/GALLON: 8.33 # GAL

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA- FLAMMABLE LIQUID -CLASS 1C LEL =2.0
DOT- FLAMMABLE LIQUID

FLASH POINT: 61 DEG.F. TAG CLOSED CUP

EXTINGUISHING MEDIA: FOAM "ALCOHOL" FOAM DRY CHEMICAL
 CO2 WATER FOG OTHER

UNUSUAL FIRE AND EXPLOSION HAZARDS : -NONE KNOWN.

SPECIAL FIRE FIGHTING PROCEDURES : WEAR SELF CONTAINED BREATHING APPARATUS WITH A FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE AND FULL BODY PROTECTIVE CLOTHING WHEN FIGHTING FIRES.

MATERIAL SAFETY DATA SHEET

PRODUCT NO. : TC320
PRODUCT NAME: SPEEDEE SPARKLE

PAGE 2 OF 2

SECTION 5 - HEALTH HAZARD DATA**EFFECTS OF OVEREXPOSURE :**

EYES: IRRITATION. POSSABLE CORNEAL INJURY.
INHALATION: HEADACHE, DROWSINESS, IRRITATION.
SKIN CONTACT: CONTACT WITH SKIN MAYBE IRRITATING.

FIRST AID PROCEDURES :

EYES: FLUSH THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.
SKIN: WASH EXPOSED AREAS WITH SOAP AND WATER. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.
INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. KEEP AT REST AND GET PROMPT MEDICAL ATTENTION.
INHALATION: REMOVE TO FRESH AIR.

SECTION 6 - REACTIVITY DATA

STABILITY: UNSTABLE STABLE
HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR
HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION OR BURNING
MAY PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.
CONDITIONS TO AVOID: HEAT, IGNITION SOURCES, FIRE.

INCOMPATIBILITY: (MATERIALS TO AVOID)- NITRIC ACID. SULFURIC ACID.
OXIDIZING AGENTS. ALDEHYDES, HALOGEN COMPOUNDS.

SECTION 7 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: FLUSH TO DRAIN WITH LARGE AMOUNTS OF WATER. LARGE SPILLS, COVER WITH SAND OR SWEEPING COMPOUND AND PICK UP INTO CONTAINERS.

WASTE DISPOSAL: ATOMIZE INTO AN INCINERATOR WHERE PERMITTED UNDER APPROPRIATE FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION 8 - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: AIR-SUPPLIED MASKS IN CONFINED AREAS.
VENTILATION: LOCAL EXHAUST-PREFERRED. MECHANICAL-ACCEPTABLE.
PROTECTIVE GLOVES: RUBBER OR PLASTIC IF PROLONGED CONTACT IS LIKELY.
EYE PROTECTION: GOGGLES OR FACE SHIELD IF SPLASHING IS LIKELY.
OTHER PROTECTIVE EQUIPMENT: NONE REQUIRED IF GOOD PRACTICES ARE FOLLOWED.

SECTION 9 - SPECIAL PRECAUTIONS**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:**

KEEP OUT OF REACH OF CHILDREN.
KEEP FROM FREEZING.
KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.
KEEP CONTAINER CLOSED WHEN NOT IN USE.

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.